

Conveyor Length Range					
		minimum		maximum	
(no supports possible)		730 mm	(28.74 in)	9144 mm	(360 in)
	with supports	984 mm	(38.74 in)	9144 mm	(360 in)
	with supports and casters	1276 mm	(50.24 in)	9144 mm	(360 in)

Conveyor Elevation Range (with C-Channel Supports)					
		minimum		maximum	
	no casters	737 mm	(29.02 in)	1143 mm	(45 in)
	with casters	864 mm	(34.02 in)	1270 mm	(50 in)

Conveyor Speed Range		
	min Hz	max Hz
VFD Frequency	20	80
MicroSpan sprockets RPM	39 RPM	156 RPM
MicroSpan Chain Speed (mm/min)	8580 mm/min	34320 mm/min
MicroSpan Chain Speed (m/min)	8.58 m/min	34.32 m/min
MicroSpan Chain Speed (ft/min)	28.1 ft/min	112.6 ft/min

Quantities of Accessories and Options							
	From (ft)	From (mm)	To (ft)	To (mm)	Supports	GR Brackets	GR Clips
(no supports possible)	2.40 ft	730 mm	3.23 ft	984 mm	0	4	0
	3.23 ft	984 mm	4.00 ft	1219 mm	2	4	0
	4.00 ft	1219 mm	6.00 ft	1829 mm	2	4	0
	6.00 ft	1829 mm	8.00 ft	2438 mm	2	6	0
	8.00 ft	2438 mm	10.00 ft	3048 mm	3	6	0
	10.00 ft	3048 mm	12.00 ft	3658 mm	3	8	0
	12.00 ft	3658 mm	14.00 ft	4267 mm	3	8	2
	14.00 ft	4267 mm	16.00 ft	4877 mm	4	10	2
	16.00 ft	4877 mm	18.00 ft	5486 mm	4	10	2
	18.00 ft	5486 mm	20.00 ft	6096 mm	4	12	2
	20.00 ft	6096 mm	22.00 ft	6706 mm	5	12	2
	22.00 ft	6706 mm	24.00 ft	7315 mm	5	14	2
	24.00 ft	7315 mm	26.00 ft	7925 mm	5	14	4
	26.00 ft	7925 mm	28.00 ft	8534 mm	6	16	4
	28.00 ft	8534 mm	30.00 ft	9144 mm	6	16	4